



METRO CASE CARTS

Specifications

- **Cart:** Type 304 Stainless Steel, No. 3 finish type.
- **Shelves:** Stainless Steel, wire (with or without roller) or solid, sold separately.
- **Bumper:** Replaceable stand-out wraparound with reinforced corners
- **Custom Orders:**
 - Extended tops for use as a back table
 - Tote boxes
 - Carts modified for elevator coupler systems
 - Carts modified for mobile assist devices.
 - Custom sizes or design
 - Over-the-road models
 - Security seal lock on doors
 - Various caster options
- **Casters:**
 - Stainless Steel: one swivel lock, two swivel with brake, one swivel on 48" model; three swivel, one swivel with brake on other models.
 - Polyurethane wheels and stainless steel horn
 - All stainless steel hardware and top plate
 - Zerk fittings with grease sealed bearings
 - 5" (127mm) diameter, 1 1/2" (38mm) face (NOTE: CASE-H36 equipped with 6" (152mm) diameter, 1 1/2" face casters).
 - Polymer: one swivel lock, two swivel with brake, one swivel on all models.
 - Advantage Thermal Plastic Rubber wheels and reinforced nylon horn
 - All stainless steel hardware and top plate
 - Self Lubricating Delrin bearing
 - 5" (127mm) diameter, 1 1/4" (32mm) round face (NOTE: CASE-H36P equipped with 6" (152mm) diameter, 1 1/2" (38mm) face casters).

Dimensions

Case Carts (shelves sold separately)

Overall		Width		Cabinet		Overall		Height		Approx. Pkd. Wt.		Cat. No. with Stainless Casters	Cat. No. with Polymer Casters
(in.)	(mm)	(in.)	(mm)	(in.)	(mm)	(in.)	(mm)	(in.)	(mm)	(lbs.)	(kg)		
32 7/8	835	28 1/2	724	38 1/4	972	28 1/2	724	115	52.27			CASE-L24	CASE-L24P
44 7/8	1140	28 1/2	724	38 1/4	972	28 1/2	724	186	84.5			CASE-L36	CASE-L36P
56 7/8	1445	28 1/2	724	38 1/4	972	28 1/2	724	212	96.4			CASE-L48	CASE-L48P
32 7/8	835	28 1/2	724	57 1/8	1451	46 1/2	1181	162	73.6			CASE-H24	CASE-H24P
44 7/8	1140	28 1/2	724	58 1/8	1476	46 1/2	1181	262	118.8			CASE-H36	CASE-H36P

All units are 28 1/2" (724mm) deep overall. Cabinet depth is 25 1/2" (648mm).

Optional Shelves (wire pullout, wire pullout with rollers, solid)

Cart	Shelf Size		Approx. Pkd. Wt. (with 2 brackets)		Cat. No. Wire Shelf	Approx. Pkd. Wt. (with 2 brackets)		Cat. No. Roller Shelf	Approx. Pkd. Wt. (with 2 brackets)		Cat. No. Solid Shelf
	(in.)	(mm)	(lbs.)	(kg)		(lbs.)	(kg)		(lbs.)	(kg)	
CASE-L24(P)	24x24	610x610	9	4.1	CCWS-24	12	5.5	CCROLWS-24	15	6.8	CCSS-24
CASE-L36(P)	24x36	610x914	13	5.9	CCWS-36	16	7.3	CCROLWS-36	19	8.6	CCSS-36
CASE-L48(P)	24x48	610x1219	19	8.6	CCWS-48	21	9.5	CCROLWS-48	25	11.3	CCSS-48
CASE-H24(P)	24x24	610x610	9	4.1	CCWS-24	12	5.5	CCROLWS-24	15	6.8	CCSS-24
CASE-H36	24x36	610x914	13	5.9	CCWS-36	16	7.3	CCROLWS-36	19	8.6	CCSS-36

Each shelf includes two attachment brackets.

Manufactured by:

InterMetro Industries Corporation
 North Washington Street, Wilkes-Barre, PA 18705
 Phone: 570-825-2741 • Fax: 570-825-2852
 For Product Information Call: 1-800-433-2232
 Visit Our Web Site: www.metro.com



L03-134
 10/07 Printed in U.S.A.

Information and specifications are subject to change without notice. Please confirm at time of order.

Copyright © 2007 InterMetro Industries Corp.

